

# WP Z-Profile

## Abmessungen



### Abmessungen

Profil	Steg h [mm]	Gurt b1 [mm]	Gurt b2 [mm]	Lippe c [mm]	Blechdicke t [mm]	Zuschnitt Z <sub>r</sub> [mm]	Gewicht g [kg/mtr]
Z 140 - 20	140	66	59	21,0	2,0	295	5,90
Z 140 - 25	140	66	59	20,5	2,5	292	5,84
Z 140 - 30	140	66	59	25,0	3,0	298	7,15
Z 160 - 20	160	71	64	30,5	2,0	344	5,50
Z 160 - 25	160	71	64	32,0	2,5	344	6,88
Z 160 - 30	160	71	64	34,0	3,0	346	8,30
Z 180 - 20	180	71	64	20,5	2,0	344	5,50
Z 180 - 25	180	71	64	22,0	2,5	344	6,88
Z 180 - 30	180	71	64	24,0	3,0	346	8,30
Z 200 - 20	200	76	69	20,0	2,0	373	5,97
Z 200 - 25	200	76	69	20,0	2,5	370	7,40
Z 200 - 30	200	76	69	24,0	3,0	376	9,02
Z 220 - 20	220	76	69	20,0	2,0	393	6,29
Z 220 - 25	220	76	69	20,0	2,5	390	7,80
Z 220 - 30	220	76	69	24,0	3,0	396	9,50
Z 240 - 20	240	81	74	20,0	2,0	423	6,77
Z 240 - 25	240	81	74	20,5	2,5	421	8,42
Z 240 - 30	240	81	74	26,0	3,0	430	10,32

Aus fertigungstechnischen Gründen sind bei den Auslauflippen (c) Maßtoleranzen möglich.

